## Dillon



## Dillon

Content > 100% Polyurethane

Backing > 70% Polyester, 30% Cotton

Finish > Antimicrobial | Silver-Based Ion Technology

Weight > 20.3 oz per linear yard

Width > 54"

Environmental > PVC Free

Benefit Phthalate | Compliant CPSC sec. 108

Lead | Compliant CPSC sec. 101

<u>Performance</u>

Abrasion > Heavy-Duty | Exceeds 200,000 Cycles

(Wyzenbeek | Cotton Duck Abradant) (ASTM D4157)

Light Fastness > Class 4/100 hrs. min. (AATCC16A)

Color Fastness > Class 5 (ASTM D3597, AATCC8) Wet

Class 5 (ASTM D3597, AATCC8) Dry

Physical Properties > Class 5 (ASTM D3511) Brush Pill

130 lbs warp, 120 lbs weft (ASTM D5034) Breaking Strength

61 lbs warp, 81 lbs weft (ASTM D4034) Seam Slippage

ISO 1419 - Pass 5 Weeks

**Flammability** 

Passes > California Tech Bulletin #117-2013

UFAC Class 1 NFPA 260 Class 1 MVSS 302 Pass IMO A. 652 (16) 8.2

Care

Cleanability > WS | Both water and solvent-based solutions

This fabric is made in China.



