

**Lounge Seating:** including; Assymble, Dialogue, Kadia, Cascade, Koncert, Odeon Series

## What to expect:

**Disassembly Time:** 15-20 minutes per chair (General)

*(allow additional 20-30 minutes for detailed component disassembly)*

**Tools needed:** Protective Equipment (Safety Glasses)

Wrenches/Ratchet w/sockets (7/16")

Screwdrivers (Phillips #2 - #3)

Utility Knife (to save time and minimize risk of injury, cut around upholstery staples, when possible)

**Material Content:**

Wood

Metal (♻️ steel)

Poly Foam

Textile (fabric/vinyl)

**Component Content:**

Upholstered Arms: (plywood frame w/staples, poly foam, textile w/staples (fabric/vinyl), legs (solid wood or (♻️ steel),

Upholstered Base (Seat/Back): (plywood frame w/staples, seat springs (♻️ steel), poly foam, textile w/staples (fabric/vinyl)

Hardware: (bolts/screws (♻️ steel))

## Lounge Series:

### **Leg Removal:**

- Place unit "upside down", remove mounting bolt (1/2" socket) for each leg



### **Arm Removal:**

- With unit upside down, use utility knife to cut the black material to allow access to mounting bolts
- .....
- Remove (4) mounting bolts (*phillips screw driver*) from the inside edge of each arm and separate from base



### **Seat Springs Removal:**

- Place unit on it's back and use utility knife to cut around staples on each end (see yellow broken line)
- Cut the black denim across the back inside rail (see far right photo), then pull back edge of seat foam forward (this will allow access to seat springs for recycling (♻️ steel))



## Lounge Series: (con't)

### Chassis Base:

#### Back Removal:

- Place unit on it's back and using 1/2" socket and/or wrench to remove (4) (nyloc) locking nuts from mountings bolts and remove back  
.....
- Remove seat panel assembly using phillips screw driver to remove (4) mounting bolts and remove seat assembly, recycle both arm and chassis (♻️ steel)

---

### Arm Cap:

- Remove (3) mounting screws (each arm)

