

SPECIFICATION SHEET

EV Collection | Mobile Healthcare Recliner - Patient Transfer Arm

E1042 | Infinite Position Non-Locking Back | Dual Removable Arm

Standard Product Information



- Urethane Arm Caps Standard
- LiquiCell® Technology
- Seat Foam Density - 2.3 HR (High Resiliency)
- Back Foam Density - 1.75 HR (High Resiliency)
- All Interior Plywood is California Carb Compliant/Phase II
- Removable Back to Clean for Infectious Disease Control
- (3) Swivel Locking Casters and (1) Rigid Locking Caster
- Mid-Ottoman Calf Support
- Infinite Position Locking or Non-Locking Back
- Standard Push Bar

Dimensions

- | | |
|-------------------------|---------|
| ▪ Width | 33.5" |
| ▪ Depth | 38" |
| ▪ Height | 47" |
| ▪ Seat Width | 24" |
| ▪ Seat Depth | 21" |
| ▪ Seat Height | 21.5" |
| ▪ Back Height | 26" |
| ▪ Arm Height | 28" |
| ▪ Cubic Feet | 26 |
| ▪ COM | 6 yds |
| ▪ Seat Depth (Kick-Out) | 40" |
| ▪ Reclined Depth | 76" |
| ▪ Weight Capacity | 650 lbs |
| ▪ Weight | 158 lbs |
| ▪ Distance from Wall | 20" |



**Designed by the Knú Design Team*

Options

- | | | | |
|-----|---|-----|--|
| U | Urethane Arm Caps | W | Wood Arm Caps |
| J | Solid Surface Arm Caps | Z | Multi Cover |
| HW | Heat Wand (Certified to UL 60601-1) | HMW | Heat & Massage Wand (Certified to UL 60601-1) |
| S4 | 4" 2-Caster Lock & Steer | Q3 | 3" Dual Wheel Central Locking Caster (Non-Directional) |
| Q4 | 4" Central Caster Lock & Steer | Q5 | 5" Central Caster Lock & Steer |
| CAL | CAL TB133 | MBB | Moisture Barrier Back |
| MBS | Moisture Barrier Seat | 4S4 | (1) 4" Swivel Locking Caster |
| AHP | Adjustable Head Rest Pillow (Requires 1 yard of fabric) | FBH | Foley Bag Holder |
| TE | Trendelenburg | FT | Foot Tray |
| EG | Edge Guard | | |

