

SPECIFICATION SHEET

EV Collection | Mobile Healthcare Recliner - Patient Transfer Arm

E2167 | Infinite Position Locking Back with Wingback | Right (facing) Fold Down Arm

Standard Product Information



- Urethane Arm Caps Standard
- LiquiCell® Technology
- Seat Foam Density - 2.3 HR (High Resiliency)
- Back Foam Density - 1.75 HR (High Resiliency)
- All Interior Plywood is California Carb Compliant/Phase II
- Removable Back to Clean for Infectious Disease Control
- (3) Swivel Locking Casters and (1) Rigid Locking Caster
- Mid-Ottoman Calf Support
- Infinite Position Locking or Non-Locking Back
- Standard Push Bar

Dimensions

- Width 33.5"
- Depth 38"
- Height 47"
- Seat Width 24"
- Seat Depth 21"
- Seat Height 21.5"
- Back Height 26"
- Arm Height 28"
- Cubic Feet 26
- COM 6 yds
- Seat Depth (Kick-Out) 39"
- Reclined Depth 76"
- Weight Capacity 650 lbs
- Weight 176 lbs
- Distance from Wall 20"



**Designed by the Knú Design Team*

Options

- | | | | |
|-----|-------------------------------------|-----|--|
| U | Urethane Arm Caps | W | Wood Arm Caps |
| J | Solid Surface Arm Caps | Z | Multi Cover |
| H | Heat (Certified to UL 60601-1) | HM | Heat & Massage (Certified to UL 60601-1) |
| HW | Heat Wand (Certified to UL 60601-1) | HMW | Heat & Massage Wand (Certified to UL 60601-1) |
| S4 | 4" 2-Caster Lock & Steer | Q3 | 3" Dual Wheel Central Locking Caster (Non-Directional) |
| Q4 | 4" Central Caster Lock & Steer | Q5 | 5" Central Caster Lock & Steer |
| CAL | CAL TB133 | MBB | Moisture Barrier Back |
| MBS | Moisture Barrier Seat | 4S4 | (1) 4" Swivel Locking Caster |
| FBH | Foley Bag Holder | IV | IV Pole and Bracket |
| TE | Trendelenburg | FT | Foot Tray |
| EG | Edge Guard | HC | Hinge Cover |
| USB | Hospital Grade Power | | |

