

SPECIFICATION SHEET

Koncert Collection | Bariatric Mobile Healthcare Recliner - Patient Transfer Arm

KB1167 | Infinite Position Locking Back | Right (facing) Fold Down Arm

Standard Product Information



- Urethane Arm Caps Standard
- LiquiCell® Technology
- Seat Foam Density - 2.3 HR (High Resiliency)
- Back Foam Density - 1.75 HR (High Resiliency)
- All Interior Plywood is California Carb Compliant/Phase II
- Removable Back to Clean for Infectious Disease Control
- (3) Swivel Locking Casters and (1) Rigid Locking Caster
- Mid-Ottoman Calf Support
- Infinite Position Locking or Non-Locking Back
- Standard Push Bar

Dimensions

- Width 38.5"
- Depth 38"
- Height 47"
- Seat Width 29"
- Seat Depth 21"
- Seat Height 21.5"
- Back Height 26"
- Arm Height 28"
- Cubic Feet 39
- COM 7 yds
- Seat Depth (Kick-Out) 40"
- Reclined Depth 73"
- Weight Capacity 750 lbs
- Weight 162 lbs
- Distance from Wall 19"



**Designed by the Knú Design Team*

Options

U	Urethane Arm Caps (Standard)	W	Wood Arm Caps
J	Solid Surface Arm Caps	Z	Multi Cover
H	Heat (Certified to UL 60601-1)	HM	Heat & Massage (Certified to UL 60601-1)
HW	Heat Wand (Certified to UL 60601-1)	HMW	Heat & Massage Wand (Certified to UL 60601-1)
S4	4" 2-Caster Lock & Steer	Q3	3" Dual Wheel Central Locking Caster (Non-Directional)
Q4	4" Central Caster Lock & Steer	Q5	5" Central Caster Lock & Steer
EG	Edge Guard	HC	Hinge Cover
CAL	CAL TB133	MB2B	Moisture Barrier Bariatric Back
MB2S	Moisture Barrier Bariatric Seat	4S4	(1) 4" Swivel Locking Caster
AHP	Adjustable Head Rest Pillow (Requires 1 yard of fabric)	FBH	Foley Bag Holder
IV	IV Pole and Bracket	FT	Foot Tray
WR	Wrist Restraint (per pair)	USB	Hospital Grade Power

