

SPECIFICATION SHEET

Rêma Collection | Manual Hydraulic Lift Treatment Recliner

R7H67 | Manual Hydraulic Lift Treatment Recliner with Right Facing Fold Down Arm and Infinite Position Locking Back

Standard Product Information



- Urethane Arm Caps Standard
- LiquiCell® Technology
- Seat Foam Density - 2.3 HR (High Resiliency)
- Back Foam Density - 1.75 HR (High Resiliency)
- All Interior Plywood is California Carb Compliant/Phase II
- Removable Back to Clean for Infectious Disease Control
- (4) 3" Dual Wheel Casters with Dual Lever Central Locking System
- Mid-Ottoman Calf Support and Orthopedic Locking Footrest
- Infinite Position Locking Back
- Standard Push Bar and Edge Guard
- Recliner lifts vertically 11-inches and reclines flat to act as a patient treatment bed

Dimensions

- | | |
|-------------------------|---------|
| ▪ Width | 39" |
| ▪ Depth | 38" |
| ▪ Height | 47" |
| ▪ Seat Width | 24" |
| ▪ Seat Depth | 21" |
| ▪ Seat Height | 21.5" |
| ▪ Back Height | 26" |
| ▪ Arm Height | 28" |
| ▪ COM | 7 yds |
| ▪ Seat Depth (Kick-Out) | 40" |
| ▪ Reclined Depth | 73" |
| ▪ Weight Capacity | 650 lbs |
| ▪ Weight | 259 lbs |
| ▪ Lift Weight Capacity | 400 lbs |
| ▪ Distance from Wall | 19" |



**Designed by the Knú Design Team*

Options

- | | | | |
|-----|-------------------------------------|-----|---|
| U | Urethane Arm Caps | W | Wood Arm Caps |
| J | Solid Surface Arm Caps | Z | Multi Cover |
| H | Heat (Certified to UL 60601-1) | HM | Heat & Massage (Certified to UL 60601-1) |
| HW | Heat Wand (Certified to UL 60601-1) | HMW | Heat & Massage Wand (Certified to UL 60601-1) |
| EG | Edge Guard | HC | Hinge Cover |
| CAL | CAL TB133 | MBB | Moisture Barrier Back |
| MBS | Moisture Barrier Seat | AHP | Adjustable Head Rest Pillow (Requires 1 yard of fabric) |
| FBH | Foley Bag Holder | IV | IV Pole and Bracket |
| TE | Trendelenburg | DP | Dual IV Poles |
| USB | Hospital Grade Power | QR | Quick Release Bracket |

